



- NOTES:**
1. ENCLOSURE MATERIAL MADE OF GRAY (RAL 7036) HOT MOLDED FIBERGLASS REINFORCED POLYESTER.
 2. UL, LISTED PER STD. 508 (FILE# E54315)
 3. CSA CERTIFIED PER STD. C222 (NO. 94; FILE# LR36508)
 4. NEMA RATED TYPE 3, 3R, 3S, 4, 4X, 12 AND 13.
 5. IEC 529 RATED IP 68.
 6. TEMPERATURE RANGES FROM -50 DEG C TO 150 DEG C.
 7. SELF EXTINGUISHING AND HALOGEN FREE.
 8. ACCESSORIES INCLUDE: BACK PANELS, DEAD FRONT PANELS, HINGED FRONT PLATES, HINGED COVERS, PRINT POCKETS, LATCHES, WINDOWS, AND VENTILATORS.
 9. CABINETS ARE MAINTENANCE FREE AND CORROSION RESISTANT.

THIS DRAWING IS THE CONFIDENTIAL AND PROPRIETARY PROPERTY OF VYNCKEER ENCLOSURE SYSTEMS, AND SHALL NOT BE REPRODUCED OR DISSEMINATED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF VYNCKEER ENCLOSURE SYSTEMS, INC.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES		VYNCKEER ENCLOSURE SYSTEMS, INC.	
DESIGNED BY KEITH CHAUHAN		DATE 2/7/01	
DRAWN BY KEITH CHAUHAN		DATE 2/7/01	
CHECKED BY DESIGN		DATE 2/7/01	
DESIGN		DATE	
SIZE	FORM NO.	DWG NO.	REV
B		VJG806HW	0
SCALE	FULL	SHEET	