



C-2000 For more information on C-2000 contactors visit gecontrolsonline.com UL File#E76233

Introducing GE's line of Lighting Contactors

Model Number	Ballast Rating	ACI Rating	Power Poles		Aux. Contacts		List
		Non-Inductive	N.O.	N.C.	N.O.	N.C.	
CL02A400T*	30A, 600 V AC 3Ø	32A	4	0	0	0	212.36
CL03A300M*	30A, 480/277 V AC 3Ø	45A	3	0	0	0	261.36
CL03A310M*	30A, 480/277 V AC 3Ø	45A	3	0	1	0	261.36
CL03A301M*	30A, 480/277 V AC 3Ø	45A	3	0	0	1	261.36
CL04A300M*	30A, 480/277 V AC 3Ø	60A	3	0	0	0	233.15
CL04A310M*	30A, 480/277 V AC 3Ø	60A	3	0	1	0	233.15
CL04A301M*	30A, 480/277 V AC 3Ø	60A	3	0	0	1	233.15
CL06A300M*	90A, 480/277 V AC 3Ø	90A	3	0	0	0	297.00
CL06A311M*	90A, 480/277 V AC 3Ø	90A	3	0	1	1	297.00

Model Number	Tungsten Rating	ACI Rating	Power Poles		Aux. Contacts		List
		Non-Inductive	N.O.	N.C.	N.O.	N.C.	
CL02A400T*	20A, 277V AC 4P	32A	4	0	0	0	212.36
CL03A300M*	30A, 480/277 V AC 3Ø	45A	3	0	0	0	261.36
CL03A310M*	30A, 480/277 V AC 3Ø	45A	3	0	1	0	261.36
CL03A301M*	30A, 480/277 V AC 3Ø	45A	3	0	0	1	261.36
CL04A300M*	30A, 480/277 V AC 3Ø	60A	3	0	0	0	233.15
CL04A310M*	30A, 480/277 V AC 3Ø	60A	3	0	1	0	233.15
CL04A301M*	30A, 480/277 V AC 3Ø	60A	3	0	0	1	233.15
CL06A300M*	60A, 480/277 V AC 3Ø	90A	3	0	0	0	297.00
CL06A311M*	60A, 480/277 V AC 3Ø	90A	3	0	1	1	297.00

To complete the Model Number replace the * with the appropriate Coil Voltage suffix from the chart below.

Coil Voltage Chart	
24V	1
120V	J
208V	L
220V	S
277V	N
480V	U
600V	Y



Your Local Representative is:

Ambient temp - 25C/+55C

Torque 15 lbs